


# PPR TORUD



TORU PPR, külmale veele 20°C/1,6 MPa . 60°C/0,8 MPa

G 8160B





d	DN	d1	s	kg/m
20	15	15,4	2,3	0,139
25	20	19,4	2,8	0,203
32	25	26,2	2,9	0,248
40	32	32,6	3,7	0,42
50	40	40,8	4,6	0,64
63	50	51,4	5,8	1
75		61,4	6,8	1,44
90	65	73,6	8,2	2,03
110	80	90	10	3,08

TORU FASER PP-RCT 20°C/2,0MPa - 70°C/1,0MPa

armeeritud klaastäite kihiga, soojale tarbeveele ja küttele

G 8200FW




d	DN	d1	s	kg/m
20	15	14,4	2,8	0,151
25	20	18	3,5	0,232
32	25	24,8	3,6	0,34
40	32	31	4,5	0,513
50	40	38,8	5,6	0,746
63	50	48,8	7,1	1,19
75		58,2	8,4	1,7
90	65	69,8	10,1	2,4
110	80	85,4	12,3	3,4

TORU STABI PP-RCT 20°C/2,0 MPa . 70°C/1,0 MPa

alumiiniumiga armeeritud, soojale tarbeveele ja küttele

G 8215B



d	DN	d1	d2	s	kg/m
20	15	14,4	21,6	2,8	0,218
25	20	19,4	26,6	2,8	0,294
32	25	24,8	33,7	3,6	0,454
40	32	31	42	4,5	0,644
50	40	38,8	52	5,6	0,935
63	50	48,8	65	7,1	1,465
75		58,2	76,8	8,4	1,929
90	65	69,8	91,8	10,1	3,011
110	80	85,4	112,7	12,3	4,288

# PPR LIITMIKUD



Pölv 45° s-v

G 8040



d
20
25
32

Pölv 45°

G 8041



d
20
25
32
40
50
63
75
90
110

Pölv 90°

G 8090



d
20
25
32
40
50
63
75
90
110

Pölv 90° s-v

G 8092



d
20
25
32

Kolmik 90°

G 8130



d
20
25
32
40
50
63
75
90
110

Kolmik üleminekuuga 90°

G 8130



d
20-25-20
25-20-25
32-20-32
32-25-32
40-20-40
40-25-40
40-32-40
50-20-50
50-25-50
50-32-50
50-40-50
63-25-63
63-32-63
63-40-63
63-50-63
75-25-75
75-32-75
75-40-75
75-50-75
75-63-75
90-63-90
90-75-90
110- 63-110
110- 75-110
110- 90-110

**Nelik**  
G 8180



d	d (värv - valge)
20	20
25	25
32	32
40	

**Muhv**  
G 8270



d
20
25
32
40
50
63
75
90
110

**Möödaviik**  
G 8287



d
20
25
32

**Kork**  
G 8301



d
20
25
32
40
50
63
75
90
110

**Liitmik**  
G 8243g



d	
20- 1/2	
20- 3/4	
25- 1/2	
25- 3/4	
32 - 1	
40-1 1/4	
50-1 1/4	
50-1 1/2	
63-2	
75-2 1/2	piiratud kogus
90-3	piiratud kogus
110-4	piiratud kogus

**Ülemineku muhv**  
G 8243



d
25-20
32-20
32-25
40-25
40-32
50-20
50-25
50-32
50-40
63-25
63-32
63-40
63-50
75-50
75-63
90-63
90-75
110-63
110-75
110-90

**Seinakinnitus**  
G 8472g



d
20- 1/2

**Liitmik**  
G 8270g



d	
20- 1/2	
20- 3/4	
25- 1/2	
25- 3/4	
32-1	
40-1 1/4	
50-1 1/4	
50-1 1/2	
63-2	
75-2 1/2	piiratud kogus
90-3	piiratud kogus
110-4	piiratud kogus

**Keevissadul**

G 8130s



d
50-25
63-25
75-25
90-25
110-25

**Flantsi otsad**

G 8790



d
40
50
63
75
90
110

**Kuulventiil**

G 8850



d
20
25
32
40
50
63
75

**Flant**

620.75.00



d
40
50
63
75
90
110

**Puur**

8986b

**Stabi torukoorija**

8977



d
16+20
20+25
32+40
50+63
75
90
110

**Keevitusaparaat**

8980/8981

**Keevitusaparaadi otsik**

8982



d
16
20
25
32
40
50
63
75
90
110

**Keevitusaparaat**

8991



8983



7
11

**Keevitusaparaadi otsik**

8984e



40
50
63
75
90
110